

Model L.TEX 8800 Series High Pressure Plunger



Maintaining reliable reproducibility of the flow rate, stability and durability, operation and use of the 8800 series pumps are very easy through the key pads on the front panel removing the rarely used functions. Especially for the most frequently accessed setting of the flow rate, the roller dial has been used for the ease of the operation. The 8800 Series offers the flow rate range up to 500ml/min. And adding the cooling jacket to the pump heads, the pump can be used for delivering super critical fluid. The SFE/SFC system can be set up using our pumps, detectors, and vessels.

L.TEX 8800 series High Pressure Plunger Pump

Model	Flow rate(ml/min)	Max. pressure	Operation
8801	0.04 ~ 3.0	40MPa	100V ~ 240V
8802	0.08 ~ 5.0	40MPa	100V ~ 240V
8803	0.2 ~ 10.0	40MPa	100V ~ 240V
8810	0.4 ~ 20.0	40MPa	100V ~ 240V
8820	0.5 ~ 30.0	35MPa	100V ~ 240V
8821	0.5 ~ 40.0	35MPa	100V ~ 240V
8822	0.5 ~ 50.0	35MPa	100V ~ 240V
8830	1.2 ~ 100.0	35MPa	100V ~ 240V
8831	2.0 ~ 150.0	35MPa	100V ~ 240V
8840	2.5 ~ 200.0	25MPa	100V ~ 240V
8842	5.0 ~ 300.0	25MPa	100V ~ 240V
8843	10.0 ~ 500.0	20MPa	100V ~ 240V

*Specifications and appearance are subject to change without any prior notice



2nd Silk Road Heights, 1721 Katakura-cho, Hachioji-shi, Tokyo 192-0914 Japan

URL: <http://l-tex.net/english/>

Tel: +81-90-4452-7824 Email: sun_inter@rc4.so-net.ne.jp

20120606-1